






<p><u>PTO Code</u> 231AR</p> <p><u>Pump Side Connection Type of PTO</u></p> 	<p><u>Main Transmission Model</u> MACK 5.08 MACK TRD 722</p>	<p>Gear Type : Flat PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,17 Mounting Location : Right and Left Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,80</p>	
<p><u>PTO Code</u> 165AE</p> <p><u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI</p> 	<p><u>Main Transmission Model</u> MACK 700 ST MACK DM 600 SX MACK DM 609 S MACK F 700 ST MACK F 700 T MACK R 607 S MACK TRD 722 MACK TRQ 7220</p>	<p>Gear Type : Flat PTO Type : Three Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,57 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 17,30</p>	
<p><u>PTO Code</u> 046AE</p> <p><u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI</p> 	<p><u>Main Transmission Model</u> MACK TRD 670</p>	<p>Gear Type : Flat PTO Type : Double Thread Torque Nm : 350 Power Kw : 36 Output Ratio 1000 Rpm : 1:1,25 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 12,00</p>	