










<p><u>PTO Code</u> 355AC2 + AC2</p> <p><u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36</p> <p>355AC3 + AC3 Shaft End Coupled With Spline 6x21x25 - UNI</p> 	<p><u>Main Transmission Model</u> MERCEDES EATON 475 SMA IVECO RENAULT VOLVO ZF</p>	<p>Gear Type : Helix PTO Type : Three Gear Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,28 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — ( Pump Shaft Rotation : Right ) Weight Kg. : 23</p>	
<p><u>PTO Code</u> 385AD</p> <p><u>Pump Side Connection Type of PTO</u> Flanged - Coupling</p> 	<p><u>Main Transmission Model</u> MERCEDES EATON FORD IVECO MAN RENAULT VOLVO ZF</p>	<p>Gear Type : Helix PTO Type : Three Gear Torque Nm : 940 Power Kw : 97 Output Ratio 1000 Rpm : 1:2,5 Mounting Location : Shaft Between Control System : Pneumatic PTO Shaft Rotation : Right and Left - (Pump Shaft Rotation Direction: Left and Right) Weight Kg. : 127,00</p>	
<p><u>PTO Code</u> 317AC2F</p> <p><u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36</p> 	<p><u>Main Transmission Model</u> RENAULT AT 2412 C RENAULT ATO 2612 VOLVO AT 26120 VOLVO DT 2412 C VOLVO V 2412 AT VOLVO V 2812 AT VOLVO VO 2512 AT VOLVO VO 3112 AT VOLVO VT 2412 B</p>	<p>Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 530 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — ( Pump Shaft Rotation : Right ) Weight Kg. : 11,00</p>	
<p><u>PTO Code</u> 325AC2F</p> <p><u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36</p> 	<p><u>Main Transmission Model</u> RENAULT AT 2412 C RENAULT ATO 2612 VOLVO AT 26120 VOLVO DT 2412 C VOLVO V 2412 AT VOLVO V 2812 AT VOLVO VO 2512 AT VOLVO VO 3112 AT VOLVO VT 2412 B</p>	<p>Gear Type : Flat PTO Type : Single Thread Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Right — ( Pump Shaft Rotation : Left ) Weight Kg. : 6,00</p>	
<p><u>PTO Code</u> 186AC2</p> <p><u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36</p> 	<p><u>Main Transmission Model</u> RENAULT B 18200 L</p>	<p>Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,72 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Right — ( Pump Shaft Rotation : Left ) Weight Kg. : 21,00</p>	