













<p><u>PTO Code</u> 230AC2</p> <p><u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36</p> 	<p><u>Main Transmission Model</u> SCANIA GR 880 VOLVO GR 870 VOLVO GR 871 VOLVO GS 760 VOLVO GS 770 VOLVO GS 771</p>	<p>Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:2,00 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — ( Pump Shaft Rotation : Left ) Weight Kg. : 20,00</p>	
<p><u>PTO Code</u> 254AC2</p> <p><u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36</p> 	<p><u>Main Transmission Model</u> SCANIA GR 900 SCANIA GRH 900 VOLVO GR 900 VOLVO GRH 900</p>	<p>Gear Type : Left Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 530 Power Kw : 55 Output Ratio 1000 Rpm : 1:0,78 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — ( Pump Shaft Rotation : Left ) Weight Kg. : 17,00</p>	
<p><u>PTO Code</u> 277AC2F</p> <p><u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36</p> 	<p><u>Main Transmission Model</u> SCANIA GR 905 SCANIA GRS 875 SCANIA GRS 895 SCANIA GRS 905 SCANIA GRS 905 R SCANIA GR50 905 SCANIA GR50 905 R</p>	<p>Gear Type : Left Helix PTO Type : Single Gear - Cardan Shaft - Double PTO Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side and Tail Control System : Pneumatic PTO Shaft Rotation : Left — ( Pump Shaft Rotation : Right ) Weight Kg. : 21,00</p>	
<p><u>PTO Code</u> 264AC2</p> <p><u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36</p> 	<p><u>Main Transmission Model</u> SCANIA GRS 890 SCANIA GRS 900 SCANIA GRS 900 R SCANIA GRS 920 R</p>	<p>Gear Type : Left Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 530 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,10 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — ( Pump Shaft Rotation : Left ) Weight Kg. : 18,70</p>	
<p><u>PTO Code</u> 345AC2F</p> <p><u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36</p> 	<p><u>Main Transmission Model</u> SCANIA GRS 895</p>	<p>Gear Type : Left Helix PTO Type : Single Gear - Cardan Shaft - Double PTO Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side and Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — ( Pump Shaft Rotation : Right ) Weight Kg. : 21,00</p>	

<p><u>PTO Code</u> 318AC2F</p> <p><u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36</p> 	<p><u>Main Transmission Model</u> SCANIA GR50 905 SCANIA GR50 905 R</p>	<p>Gear Type : Left Helix PTO Type : Single Gear - Cardan Shaft - Double PTO Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side and Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — ( Pump Shaft Rotation : Right ) Weight Kg. : 21,00</p>	
---	---	--	---