PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
355AC2 + AC2 355AC3 + AC3	Square Flange ISO 14 - DIN 5462 - 8x32x36 Shaft End Coupled With Spline 6x21x25 - UNI	MERCEDES EATON 475 SMA IVECO RENAULT VOLVO ZF	Gear Type : Helix PTO Type : Three Gear Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,28 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 23	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
385AD	Flanged - Coupling	MERCEDES EATON FORD IVECO MAN RENAULT VOLVO ZF	Gear Type : Helix PTO Type : Three Gear Torque Nm : 940 Power Kw : 97 Output Ratio 1000 Rpm : 1:2,5 Mounting Location : Shaft Between Control System : Pneumatic PTO Shaft Rotation : Right and Left - (Pump Shaft Rotation Direction: Left and Right) Weight Kg. : 127,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
048AC2F	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES 2067	Gear Type : Flat PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
067BE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 2-24 MERCEDES 309	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 320 Power Kw : 33 Output Ratio 1000 Rpm : 1:1,29 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
116BE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 309 MERCEDES 309	Gear Type : Left Helix PTO Type : Single Thread Torque Nm : 240 Power Kw : 25 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 7,00	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
217AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 100-1 MERCEDES G 100-12 MERCEDES G 100-13 MERCEDES G 100-2 MERCEDES G 100-9 MERCEDES G 140-6 MERCEDES G 140-8	Gear Type : Flat PTO Type : Single Gear Torque Nm : 520 Power Kw : 54 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,00		
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
224AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 100-1 MERCEDES G 100-12 MERCEDES G 100-13 MERCEDES G 100-2 MERCEDES G 100-9 MERCEDES G 140-6 MERCEDES G 140-8	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,00		
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
235AE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 100-1 MERCEDES G 100-12 MERCEDES G 100-13 MERCEDES G 100-2 MERCEDES G 100-9 MERCEDES G 140-6 MERCEDES G 140-8	Gear Type : Helix PTO Type : Double Gear Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,50		
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
218AC2F	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 131-9 MERCEDES G 141-9 MERCEDES G 211-12 MERCEDES G 211-16 MERCEDES G 221-9 MERCEDES G 230-12 MERCEDES G 230-16 MERCEDES G 240-16	MERCEDES G 260-16 MERCEDES G 280-16 MERCEDES G 281-12 MERCEDES G 330-12	Gear Type : Düz PTO Type : Single Gear - Cardan Shaft Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,40	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
243AC2F	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 131-9 MERCEDES G 141-9 MERCEDES G 211-12 MERCEDES G 211-16 MERCEDES G 221-9 MERCEDES G 230-12 MERCEDES G 230-16 MERCEDES G 240-16	MERCEDES G 260-16 MERCEDES G 280-16 MERCEDES G 281-12 MERCEDES G 330-12	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 425 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 20,00	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
245AEF	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 131-9 MERCEDES G 141-9 MERCEDES G 211-12 MERCEDES G 211-16 MERCEDES G 221-9 MERCEDES G 230-12 MERCEDES G 230-16 MERCEDES G 240-16	MERCEDES G 260-16 MERCEDES G 280-16 MERCEDES G 281-12 MERCEDES G 330-12	Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 425 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 17,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
169AC2F	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 155-16 MERCEDES G 155-9 MERCEDES G 180-16 MERCEDES G 210-16		Gear Type : Flat PTO Type : Single Gear - Cardan Shaft Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 7,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
244AC2F	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 155-16 MERCEDES G 155-9 MERCEDES G 180-16 MERCEDES G 210-16		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 425 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 17,60	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
246AEF	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 155-16 MERCEDES G 155-9 MERCEDES G 180-16 MERCEDES G 210-16		Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 425 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 16,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
067BE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 2-24 MERCEDES 309		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 320 Power Kw : 33 Output Ratio 1000 Rpm : 1:1,29 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
136AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Flat PTO Type : Single Gear Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 3,70	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
139AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Flat PTO Type : Double Gear Torque Nm : 550 Power Kw : 57 Output Ratio 1000 Rpm : 1:1,24 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
220AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,10	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
229AE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Helix PTO Type : Double Gear Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,10	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
280AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Flat PTO Type : Single Thread - Pump Side Sealing Seal Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 5,00	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
387AC2M	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Flat PTO Type : Double Gear - Pump Side Sealing Seal - Switch Torque Nm : 550 Power Kw : 57 Output Ratio 1000 Rpm : 1:1,56 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,50	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
388AC2M	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Flat PTO Type : Double Gear - Pump Side Sealing Seal - Switch Torque Nm : 550 Power Kw : 57 Output Ratio 1000 Rpm : 1:1,70 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,50	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
390AD	Flanged - Coupling	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Flat PTO Type : Four Gear - 4x4 Torque Nm : 550 Power Kw : 57 Output Ratio 1000 Rpm : 1:1,1 Mounting Location : tail type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,20	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
014AE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 3/50 MERCEDES G 5/75 MERCEDES G 51302 MERCEDES G 52302		Gear Type : Flat PTO Type : Single Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 5,80	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model			
014BL	Shaft Output Pin Hole	MERCEDES G 3/50 MERCEDES G 5/75 MERCEDES G 51302 MERCEDES G 52302		Gear Type : Flat PTO Type : Single Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 6,00	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
202AE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 3/50 MERCEDES G 5/75 MERCEDES G 51302 MERCEDES G 52302	Gear Type : Helix PTO Type : Double Gear Torque Nm : 220 Power Kw : 23 Output Ratio 1000 Rpm : 1:1,31 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 12,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
142ADF	Flanged - Coupling	MERCEDES G 3-65 MERCEDES G 3-90	Gear Type : Flat PTO Type : Single Gear - Cardan Shaft Torque Nm : 280 Power Kw : 29 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
016AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 4 110 MERCEDES G 4 65 MERCEDES G 4 90 MERCEDES G 4 95 MERCEDES G 6 90	Gear Type : Flat PTO Type : Single Thread Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 6,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
249AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 4 110 MERCEDES G 4 65 MERCEDES G 4 90 MERCEDES G 4 95 MERCEDES G 6 90	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
250AE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 4 110 MERCEDES G 4 65 MERCEDES G 4 90 MERCEDES G 4 95 MERCEDES G 6 90	Gear Type : Helix PTO Type : Double Gear Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,00	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
290AE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 56-6	Gear Type : Helix PTO Type : Double Thread Torque Nm : 420 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
291AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 56-6	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 420 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,00	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
006AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 60-6 MERCEDES G 71-6 MERCEDES G 85-6 MERCEDES G 90-6	Gear Type : Flat PTO Type : Single Thread Torque Nm : 600 Power Kw : 62 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 5,70	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
225AC2	Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 60-6 MERCEDES G 71-6 MERCEDES G 85-6 MERCEDES G 90-6	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 420 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,20	
PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
236AE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 60-6 MERCEDES G 71-6 MERCEDES G 85-6 MERCEDES G 90-6	Gear Type : Helix PTO Type : Double Gear Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,70	

PTO Code	Pump Side Connection Type of PTO	Main Transmission Model		
158BE	6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES MB 700 MERCEDES MB 800 ZF S 5- 42	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00